

# QinetiQ



NOTIFIED BODY  
No 0191

## CERTIFICATE OF TYPE APPROVAL

(EC Certificate of Type Examination - Module B)  
(Marine Equipment Directive - 96/98/EC)

### Applicant:-

Northrop Grumman Sperry Marine B.V.  
118 Burlington Road, New Malden  
Surrey, KT3 4NR  
United Kingdom

### Manufacturer:-

Northrop Grumman Sperry Marine B.V.  
118 Burlington Road, New Malden  
Surrey, KT3 4NR  
United Kingdom

This is to certify that the applicant has submitted details of a:-

**Shipborne Radar Equipment with Electronic Plotting Aid (EPA)**  
(COMMISSION DIRECTIVE 2002/75/EC – ITEM A.1/4.36)

Of system type known and designated as:-

- a) **Bridgemaster E, EPA18 - 180mm Display, X-Band Radar/EPA Systems**
- b) **Bridgemaster E, EPA18 - 180mm Display, S-Band Radar/EPA Systems**

(Comprising component parts and having technical characteristics shown in schedules 1 to 3) and that these have been assessed, tested and when used in a combination of component parts as described in the attached schedules, is CERTIFIED as complying with the relevant parts of:

- EN 60936-1:2000, "Marine Shipborne Radar Equipment"**
- EN 60872-3:2001, "Electronic Plotting Aids (EPA)"**
- EN 60945 : 1997, "General Requirements for Marine Navigation Equipment"**

(being European Standards for Technical Characteristics and Methods of measurements equivalent to IEC 60936-1, IEC 60872-3 and IEC 945, published by the International Electrotechnical Commission).

It is also RECOGNISED that the equipment conforms to performance standards not inferior to those adopted by the International Maritime Organisation, and which are contained in the relevant parts of Resolution MSC 64(67) Annex 4 and Resolution A694(17).

Notified Body 0191

SIGNED:

DATE of ISSUE:

4<sup>th</sup> June 2004

DATE of EXPIRY:

11<sup>th</sup> June 2008

P J Goddard Authorised Signatory

Certificate Number:

QQ-MED-32/03-02R

This Certificate is Valid until expiry date shown, subject to the standard conditions of issue printed on the attached schedule

Sperry Marine are Module D registered with QinetiQ, ref;  
Certificate DQAS-16/04-NGS001 & Condition 3.

QinetiQ  
Fraser Range  
Fort Cumberland Road, Eastney  
Portsmouth, Hampshire. PO4 9LJ



Maritime and Coastguard Agency  
The MCA is an Executive Agency of  
the Department for Transport

*Under the terms of the United Kingdom Statutory Instrument, No 1957 : 1999, the QinetiQ Group PLC (formerly known as DERA) has been Notified to the European Commission by the Maritime and Coastguard Agency as a Body authorised to conduct Conformity Assessment procedures under the provisions of the European Council Directive 96/98/EC on Marine Equipment and issue Certificates of Type Approval.*

# Certificate of Type Approval - Schedule 1

## Bridgemaster E, EPA18 - 180mm, X-Band Radar/EPA System

The applicant declared that the following units comprise the radar equipment of the system designation a) given above. These units have been assessed & tested, and satisfactory details of these units were included in the technical file. These units form systems consistent with the Item Description A1/4.36, given in Annex A1 of Commission Directive 2002/75/EC.

**MAIN UNIT** Comprising:-

Radar Display - LCD Monitor	65815A, C or D	
or Radar Display - CRT Monitor	65814#	*1
Processor - Radar/EPA	65800PA#◇ or PD#◇	*2, 3
Transceiver/Turning Unit (10kW)	65810#A# or #D#	*4, 5, 6
or Transceiver/Turning Unit (25kW)	65825#A#	*4, 5, 6
or Transceiver Bulkhead (10kW)	65810A, B, E, F, G, H, L, P, T or W	
or Transceiver Bulkhead (25kW)	65825A, B, E, F, G, H, L, P, T or W	
and Turning Unit	65801BAR or CA#	*5, 6
X-Band Antenna (4, 6 or 8ft)	65604A or 65606A or 65608A	
<b>SOFTWARE:-</b> Main System Software	Version C5.02	*7

----- End of List -----

And which may include any item or combination of items from the list of optional items found in schedule 3 on sheet 4.

**NOTES:-**

- 1 A 1st letter (#) suffix (F, N, R, or Y) is used to denote buffered O/P and mounting/case style.
- 2 A 3rd letter (¤) suffix (R, or V) is used to denote the choice of Compass option.
- 3 A 4th letter (◇) suffix (E, F, G, H, J, K, L, or R) is used to denote the choice of mount and controls which may include Keyboard, Joystick, Rollerball and Memory card facilities.
- 4 A 1st letter (#) suffix (M, N, P, T or W) is used to denote the choice Bias limiter, extra short pulse transmit or additional facilities
- 5 A 3rd letter (¤) suffix (R, T or U) is used to denote the choice of pulse or syncro azimuth signal.
- 6 This item is link selectable on installation to 24 or 48 RPM antenna speed
- 7 This approval remains valid for equipment including subsequent Minor software amendments, as allowed by the C5.xx format (xx represents numerals), where written details of any such modifications have been submitted to and accepted by QinetiQ.

**Technical Characteristics**

FREQUENCY OF OPERATION	9.410 GHz	±30MHz
PULSE REPETITION FREQUENCY (PRF)	1800, 1800, 785	3000 on 'G', 'L', 'P' & 'T' 1 <sup>st</sup> Suffix TxRx
PULSE LENGTHS	0.05µs, 0.25µs, 0.75µs	
EMISSION CODE	3M00PONAN	
POWER CHARACTERISTIC	10kW or 25kW	(PEP)
RADAR DISPLAY CIRCLE	≥250mm	Effective Diameter
IEC 61162-1 SERIAL (NMEA) PORTS	Listner - 2 Talker - 2	Conformity to IEC 61162-1:2000. Optional serial interface unit available
TEMPERATURE RANGE Exposed & IEC 60945 CLASS Protected	-25°C to +70°C -15°C to +55°C	-- Turning Units & Antenna -- All other units
POWER SOURCE	100-240V AC, 50/60Hz 24V DC	

**Conditions of Issue of this certificate are printed the reverse of sheet 5.**

QinetiQ  
Fraser Range  
Fort Cumberland Road, Eastney  
Portsmouth, Hampshire. PO4 9UJ

Certificate Number    **QQ-MED-32/03-02R**



## Certificate of Type Approval - Schedule 2

### Bridgemaster E, EPA18 - 180mm, S-Band Radar/EPA System

The applicant declared that the following units comprise the radar equipment of the system designation b) given above. These units have been assessed & tested, and satisfactory details of these units were included in the technical file. These units form systems consistent with the Item Description A1/4.36, given in Annex A1 of Commission Directive 2002/75/EC.

MAIN UNIT Comprising:-

Radar Display - LCD Monitor	65815A, C or D	
or Radar Display - CRT Monitor	65814 $\pi$ ,	*1
Processor - Radar/EPA	65800PA $\ddagger$ $\diamond$	*2, 3
Transceiver/Turning Unit (30kW)	65830M $\S$ R or N $\S$ $\neq$	*4, 5
or Bulkhead Transceiver (30kW)	65831A or B	
and Turning Unit	65830B $\S$ R or C $\S$ $\neq$	*4, 5,
Scanner Control Unit	65837A $\emptyset$	*6
S-Band Antenna 12ft	65612A	
SOFTWARE:- Main System Software	Version C5.02	*7

----- End of List -----

And which may include any item or combination of items from the list of optional items found in schedule 3 on sheet 4.

NOTES:-

1. A 1st letter ( $\pi$ ) suffix (F, N, R, or Y) is used to denote buffered O/P and mounting/case style
2. A 3rd letter ( $\ddagger$ ) suffix (R, or V) is used to denote the choice of Compass option.
3. A 4th letter ( $\diamond$ ) suffix (E, F, G, H, J, K, L, or R) is used to denote the choice of mount and controls which may include Keyboard, Joystick, Rollerball and Memory card facilities.
4. A 2nd letter ( $\S$ ) suffix (E, F, G, H, J, K, L, M, P, Q, R or S) is used to denote the choice of operating voltage and 24 or 48 RPM antenna speed.
5. A 3rd letter ( $\neq$ ) suffix (R, T or U) is used to denote the choice of pulse and/or syncro azimuth signal.
6. A 2<sup>nd</sup> letter ( $\emptyset$ ) suffix (B, C, E, F or H) is used to denote the choice of operating voltage and 24 or 48 RPM antenna speed.
7. This approval remains valid for equipment including subsequent Minor software amendments, as allowed by the C5.xx format (xx represents numerals), where written details of any such modifications have been submitted to and accepted by QinetiQ.

#### Technical Characteristics

FREQUENCY OF OPERATION	3.050 GHz	$\pm$ 10MHz
PULSE REPETITION FREQUENCY (PRF)	1800, 1800, 785	
PULSE LENGTHS	0.05 $\mu$ s, 0.25 $\mu$ s, 0.75 $\mu$ s	
EMISSION CODE	3M00PONAN	
POWER CHARACTERISTIC	30kW	(PEP)
RADAR DISPLAY CIRCLE	$\geq$ 250mm	Effective Diameter
IEC 61162-1 SERIAL (NMEA) PORTS	Listner - 2 Talker - 2	Conformity to IEC 61162-1:2000. Optional serial interface unit available
TEMPERATURE RANGE Exposed & IEC 60945 CLASS Protected	-25°C to +70°C -15°C to +55°C.	-- Turning Units & Antenna -- All other units
POWER SOURCE	100-240V AC, 50/60Hz	Turning Unit can be 1 or 3 phase

**Conditions of Issue of this certificate are printed the reverse of sheet 5.**

QinetiQ  
Fraser Range  
Fort Cumberland Road, Eastney  
Portsmouth, Hampshire. PO4 9UJ

Certificate Number **QQ-MED-32/03-02R**

## Certificate of Type Approval - Schedule 3

### Bridgemaster E Radar Systems - Ancillary and Optional Units

The applicant declared that the following units may be added to the basic radar systems illustrated in schedules 1 & 2. These units have been assessed & tested in conjunction with various Sperry Marine, Bridgemaster E, systems, and satisfactory details were included in the technical file.

#### ANCILLARY UNITS:-

6 way Interswitch Unit (6x6)	65846A	
2 way Interswitch Unit (2x4)	65842A	
Serial Interface Unit	65847A	
Serial Interface adapter	65848A	
Slave Junction Box	65849A	
Transceiver Compatibility Unit	65841A or D	*1, 2
Display Compatibility Unit	65840A	*1, 3

#### MODULAR UNITS :-

Keyboard	65845600	*4
Memory Card	65821619 or 65826655	*4
Trackerball	65821623 or 65826654	*4
Joystick	65821620 or 65826658	*4
Brilliance Control	65821621 or 65826657	*4
On/Off Switch	65826656	*4

----- End of List -----

#### \* NOTES:-

- 1 Units required when interfacing Bridgemaster E system to existing legacy equipment onboard.
- 2 Used when interfacing Bridgemaster II radar transceiver to a Bridgemaster E Display.
- 3 Used when interfacing Bridgemaster II Display to a Bridgemaster E radar transceiver.
- 4 These units are identified individually when the Kit Form Processors and Monitors are used in a system



**Notified Body 0191**

**Conditions of Issue of this certificate are printed the reverse of sheet 5.**

QinetiQ  
Fraser Range  
Fort Cumberland Road, Eastney  
Portsmouth, Hampshire. PO4 9LJ

**Certificate Number**    **QQ-MED-32/03-02R**

## Certificate of Type Approval - Schedule 4

### Statement on Spurious and Out of Band Emissions and the Boundary between these emissions

The following Radar Transceivers, which form part of the systems shown on earlier schedules, have been subject to a measurement procedure as detailed in IEC 60936-1, Annex D, as contained in Amendment 1, dated July 2002 and the guidelines contained in ITU-R Recommendation M.1177. This standard defines the test method and requirements for shipborne radar to meet in order to comply with Appendix S3 of the Radio Regulations and ITU-R Recommendations SM.1539 and SM.1541. The results of the measurement procedure were satisfactory and provide sufficient evidence that these Radar Transceivers are compliant with the criteria contained in the stated standards.

The Transceivers Measured were:-

Description	Model No.	Modulator PCB	Magnetron
Transceiver/Turning Unit (10kW)	65810### *1	65810812	MG5473
or Transceiver/Turning Unit (25kW)	65825### *1	65825812	MG 5424
Transceiver/Turning Unit (30kW)	65830### *1	65830812	MG5223 or M1302A

The test reports detailing the tests and test results obtained are:-

QinetiQ/FST/CMT/CR012225  
QinetiQ/FST/CMT/TR022173

These also detail the magnetron, modulator circuit, rotary joint\*2 and any filters fitted to the test unit to which the results specifically apply.

The Transceiver Modules contained in the above Transceiver/Turning units are also found in the following Bulkhead units. Since the applicable electronic circuitry and component parts are identical and the addition of the waveguide/helix feeder is known to have band limiting properties, a presumption of conformity can be applied by analogy

Transceiver Bulkhead (10kW)	65810#*1
Transceiver Bulkhead (25kW)	65825#*1
Bulkhead Transceiver (30kW)	65831#*1

- Note \*1 The symbol # or ### denotes a 1 or 3 letter suffix detailing aspects of the build standard. Details of the suffixes are provided on the appropriate equipment schedule pages.
- \*2 The manufacturer declared that the build standard of the rotary joint is suitably defined by the turning unit designation.

**Conditions of Issue of this certificate are printed overleaf.**

QinetiQ  
Fraser Range  
Fort Cumberland Road, Eastney  
Portsmouth, Hampshire. PO4 9LJ

Certificate Number **QQ-MED-32/03-02R**